

Cable Termination Accessories

Stainless Steel Cable Ties

KABEX Stainless Steel Cable Ties are Grade 316 Stainless and available in coated or uncoated versions, Standard widths of 4.6 mm or 7.9 mm and available in various lengths.

This tie is of a roller-ball design which is self locking and fast & easy to install. It can be tightened by hand or with a special tool.

The normal operating range for the roller ball uncoated ties version is -80C to +538C approximately. For coated version normal operating range is -80C to +150C.

Fully coated roller ball tie (Patent Pending) is recommended for extreme cold conditions and offshore applications.

Coating is non toxic halogen free Polyester. It is available in wide choice of colours.



Stainless Steel Cable Ties

Type: Roller Ball

Grade : SS316

Part Number	Description	Length mm	Width mm	Max Bundle Dia mm
ST125	125 x 4.6mm Stainless Steel Uncoated	100	4.6	16
ST150	150 x 4.6mm Stainless Steel Uncoated	150	4.6	32
ST200	200 x 4.6mm Stainless Steel Uncoated	150	4.6	50
ST360	360 x 4.6mm Stainless Steel Uncoated	360	4.6	100
ST520	520 x 4.6mm Stainless Steel Uncoated	520	4.6	150
ST200H	200 x 7.9mm Stainless Steel Uncoated	200	7.9	50
ST360H	360 x 7.9mm Stainless Steel Uncoated	360	7.9	100
ST520H	520 x 7.9mm Stainless Steel Uncoated	520	7.9	150
ST680H	680 x 7.9mm Stainless Steel Uncoated	680	7.9	200
ST1000H	1000 x 7.9mm Stainless Steel Uncoated	1000	7.9	300
ST200C	200 x 4.6mm Stainless Steel Coated	520	4.6	150
ST360C	360 x 4.6mm Stainless Steel Coated	680	4.6	200
ST200HC	200 x 7.9mm Stainless Steel Coated	520	7.9	150
ST360HC	360 x 7.9mm Stainless Steel Coated	680	7.9	200

Other sizes available for Coated Versions upon request

Minimum Loop Tensile Strength:

4.6 mm width Un-coated (44.5 kg) 100 lbs

7.9 mm width Un-coated (111.2 kg) 250 lbs

4.6 mm width Coated (44.5 kg) 100 lbs

7.9 mm width Coated (55 kg) 120 lbs