

Cable Termination Accessories

IP68 NYLON CABLE GLAND

UL Approved Nylon 66, 94V-2
IP68 Rating
Halogen Free
ROHS Compliant



Part Number	Thread	Cable OD: (mm)	Std Pack
MG12	M12	3 - 6.5	50
MG16	M16	5 - 10	50
MG20	M20	10 - 14	30
MG25	M25	13 - 18	16
MG32	M32	18 - 25	12
MG40	M40	22 - 32	6
MG50	M50	30 - 38	3
MG63	M63	34 - 44	2

For braided EMC cable

Part number	Thread	Cable OD (mm)
G16EMC	M16	5 - 9
G20EMC	M20	8 - 13
G25EMC	M25	11 - 17
G32EMC	M32	15 - 21
G40EMC	M40	19 - 28
G50EMC	M50	26 - 35
G63EMC	M63	32 - 42



EMC Lockunt

Part number	Thread
LN16EMC	M16
LN20EMC	M20
LN25EMC	M25
LN32EMC	M32
LN40EMC	M40
LN50EMC	M50
LN63EMC	M63

Cable Gland for Flat Cables

Part number	Thread	Cable Width in mm	Cable Thick. in mm
FG32	M32	Min. 14/27 Max.	Min. 4/11.5 Max.
FG40	M40	Min. 24/34 Max.	Min. 4/11.5 Max.
FG50	M50	Min. 29/44 Max.	Min. 5/12.0 Max.
FG63	M63	Min. 34/50 Max.	Min. 5/12.0 Max.